




US Army Corps
of Engineers

Detroit District


Study Objectives

- Application of SWAT model to examine sediment yield over last 175 years and examine trapping efficiency of federal harbor




US Army Corps
of Engineers

Detroit District




Source: Google Earth


Watershed Location and Drainage Area




Watershed Topography




Land Cover -1992



Distribution of Cropland






US Army Corps
of Engineers

Detroit District

Present St. Joseph Harbor



Source: USACE, Detroit





US Army Corps
of Engineers
Detroit District

Temporal Changes to Sediment Supply

Model sediment yield over last 175 years and examine trapping efficiency of federal harbor and incorporate the following land use changes:

- < 1840 – very little human impact
- 1850 - Intense logging begins
- > 1850 – watershed converted to ag use.
- > 1850 – dams built to support logging and agriculture



Logging and Sediment

US Army Corps
of Engineers

Detroit District



From Dickmann and Leefers, 2003



Logging and Sediment

US Army Corps
of Engineers

Detroit District



From Dickmann and Leefers, 2003




US Army Corps
of Engineers

Detroit District

Models Applied



Acronym	Model Name	Agency	Processes
SWAT	Soil Water Assessment Tool	USDA / EPA	Hydrology Soil Erosion Sediment Delivery
GSSHA	Gridded Surface- Subsurface Hydrologic Analysis	USACE	Hydrology (1-D River Hydrodynamics) Sediment Transport Sediment Yield Sediment Delivery
RMA2- SED2D	RMA2-SED2D	USACE- WES	2-D River Hydrodynamics; Sediment Erosion, Transport and Deposition

Dams




SWAT Model Input


Land Use



Elevation



Soils




Climate



US Army Corps
of Engineers

Detroit District

SWAT Calibration/Validation






US Army Corps
of Engineers

Detroit District

Pre-European Settlement Landcover

In Dickmann and Leefers, 2003






US Army Corps
of Engineers

Detroit District

Land Cover Change




Land Cover Change


St. Joseph Watershed

Land Use Change

Effects on Sediment Loading




Pre-development



SDA *SWAT Edition*

www.Baird.com



1992




US Army Corps
of Engineers

Detroit District

SWAT Land Cover Change Results

Year	Model Condition	Total Soil Erosion in the Watershed (m ³ per year)
1830	Pre-Development	55,000
1992	Present Land Use	676,000


Improved Farmland by County





US Army Corps
of Engineers
Detroit District

Sediment Delivery Estimates






US Army Corps
of Engineers

Detroit District


Influence of Dams

- ◆ St. Joseph Watershed: 65 major dams and 125 minor dams constructed since 1850s
- ◆ Dams intercept most coarse sediment
- ◆ 87% of watershed upstream from major dams
- ◆ SWAT used to determine likely effect of dams on sediment supply to the harbor

Influence of Dams



SWAT: Dam Scenario Results





SDA *SWAT Edition*

www.Baird.com

Effect of Dams

on Sediment Delivery to St. Joseph Harbor






Influence of Dams

US Army Corps
of Engineers

Detroit District

Crossmark on Axis Shows Location of Major Dam





US Army Corps
of Engineers

Detroit District


Influence of Dams

Year	Model Conditions	Total Soil Erosion in the Watershed (m ³ per year)	Total Sediment at Mouth of Paw Paw (m ³ per year)	Total Sediment at Harbor Mouth (m ³ per year)
1992	Reference Condition	675,000	11,000	44,000
1992	No dams or reservoirs	675,000	11,000	216,000

(44,000 m³ = 57,000 yd³)


Sediment Transport Modeling


Harbor Trapping





3 mile u/s, 1 mile offshore











Concentration
mg/l

0.00200
0.00100
0.00000

St. Joseph Harbor
Mean Lake Level
Mean Paw Paw Flow
High St. Joes Flow
(300-470 cms)

Baird

400 0 400 m

RMA2 Results

2002 bathymetry - no dredging (present condition)

Time Period	Duration (Years)	% Leaving Inner Harbor	% Deposited in Inner Harbor
Oct 1930- Sept 2003	73	45%	55%
Jan 1980 - Dec 2000	21	48%	52%
Jan 1978 - Dec 1997	20	48%	52%
Jan 1988 - Dec 1997	10	33%	67%


2002 bathymetry - inner harbor dredged to 20 feet

Time Period	Duration (Years)	% Leaving Inner Harbor	% Deposited in Inner Harbor
Oct 1930- Sept 2003	73	46%	54%
Jan 1980 - Dec 2000	21	50%	50%
Jan 1978 - Dec 1997	20	50%	50%
Jan 1988 - Dec 1997	10	34%	66%

1907 bathymetry

Time Period	Duration (Years)	% Leaving Inner Harbor	% Deposited in Inner Harbor
Oct 1930- Sept 2003	73	54%	46%
Jan 1980 - Dec 2000	21	57%	43%
Jan 1978 - Dec 1997	20	57%	43%
Jan 1988 - Dec 1997	10	44%	56%

Harbor Dredging Records





US Army Corps
of Engineers

Detroit District

Conclusions

- ◆ Present sediment production is an order of magnitude greater than during Pre-European settlement of the watershed (675,000 m³/yr vs. 55,000 m³/yr).
- ◆ Dams are presently storing 80% of sediment delivered to the stream.
- ◆ The effect of land-use changes is offset by the addition of dams

Questions?

**Dr. Jim Selegean, P.E., P.H.
U.S. Army Corps of Engineers, Detroit District
Great Lakes Hydraulics and Hydrology Office
477 Michigan Ave
Detroit, MI 48226
313.226.6791**

james.p.selegean@usace.army.mil